



Technical Specifications		EN 60118-0	EN 60118-7:2005
		Ear Simulator	2ccm-coupler
Output (OSPL90)			
Max	dB SPL	145	140
HFA Avg (1000,1600,2500 Hz)	dB SPL	138	131
Gain (FOG50)			
Max	dB	88	80
HFA Avg (1000,1600,2500 Hz)	dB	78	70
Reference Test Gain (Input 60 dB SPL)		60	52
EQ Input Noise		23	24
Frequency Response (RESP60)			
Low Frequency Limit	Hz	100	100
High Frequency Limit	Hz	5600	5500
Total Harmonic Distortion			
500 Hz (Input 70 dB SPL)	%	-	-
800 Hz (Input 70 dB SPL)	%	0.4	0.2
1600 Hz (Input 75 dB SPL)	%	0.5	0.4
Battery (1000 Hz / Input 65 dB)			
Battery Life (Avg) (*)	Hour	18	
Battery Type		Lithium-Ion	
EQ Band		12	
Number of programs		4	
WDRC channels		6	
Frequency channels		12	
Microphone		2	
Touch Button (VC/Prog/AirPlane/Device on-off)		Multifunctional	

* The usage time of the rechargeable battery varies depending on the following features;
* Streaming using * Regular hearing instrument

Key Features:

- 30 Compression Application Parameters
- 12 Frequency Channels
- 24 kHz Sampling Frequency
- 6 MPO Output Limits
- 12 EQ Bands
- Up to 12kHz Fitting Bandwidth*
- 4 Programs
- 6 WDRC Channels
- Noise Reduction
- FBC (FeedBack Canceller)
- Program Change Warning (Voice or Tone)
- Low Battery Warning (Voice or Tone)
- Volume Control
- Starting Program/Volume Memory
- Datalogging
- Activation Delay
- Fitting Formula Settings (NAL-NL2, DSL Adult/Pediatrics)

* Bandwidth is available in Gain Adjustments in Fitting software.


- Frequency Channel and WDRC Channel Independent Adaptation
- Mobile Parameter Setting (Cleverear)
- AirPlane Mode
- EarToEar Connectivity
- Bluetooth® Control
- Rechargeable Battery

Performance Features:


Extra safety and durability tests:
Eartechnic hearing devices are reliable, durable and robust with its unique design.

- IEC 60068-2-64 (Vibration)
- IEC 60068-2-31 (Mechanical shocks)
- IEC 60068-2-14 (Shock temperature changes)
- IP68 (IEC 60529) (Dust, water and humidity)


Fitting Range



EN 60118-0 Ear Simulator



EN 60118-7:2005 2ccm-coupler



- **OSPL** (Output Sound Pressure Level) / **RESP** (Frequency Response)
- **FOG** (Full On Gain)

• Technical datas are given in according to EN 60118-0 Ear Simulator (MZ coupler) / EN 60118-7:2005 2ccm-coupler values.

- The hearing aid's maximum output sound level can exceed 132 dB SPL.
- Selecting and fitting of the instrument can only be done by a specialist as there is a risk of impairing the residual hearing of the user.

Programming System

Wireless Programming
FitLine

